ROC920030312US1
10/728,017

3

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A method comprising:

   receiving an operation, a selection of a block of code, and a selection of a paste location;

   determining that the ~~whether a~~ block of code ~~associated with an operation~~ has a size greater than a ~~threshold; and~~threshold;

   ~~when the size is greater than the threshold,~~ creating a method that comprises the block of code; and

   adding an invocation of the method at the paste location.

2. (Original) The method of claim 1, further comprising:

   replacing the block of code at a copy location with an invocation of the method.

3. (Canceled)

4. (Original) The method of claim 1, further comprising:

   displaying user interface options based on whether the operation is to be performed within a single part and class.

5. (Original) The method of claim 1, further comprising:

   displaying user interface options based on whether the operation is to be performed between two parts in a single package.

6. (Original) The method of claim 1, wherein the operation comprises a copy-and-paste operation.

7. (Original) The method of claim 1, wherein the operation comprises a punch-out operation.

ROC920030312US1   4
10/728,017

8. (Currently amended) An apparatus comprising:

means for receiving a copy-and-paste operation, a selection of a block of code, and a selection of a paste location;

means for determining that the~~whether a~~ block of code ~~associated with a copy-and-paste operation~~ has a size greater than a threshold;

means for creating a method that comprises the block of code ~~when the size is greater than the threshold~~; and

means for replacing the block of code with an invocation of the method.

9. (Currently amended) The apparatus of claim 8, further comprising:

means for adding the invocation of the method at the paste ~~a paste~~ location.

10. (Original) The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on whether the copy-and-paste operation is within a single part and class.

11. (Original) The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on whether the copy-and-paste operation is between two parts in a single package.

12. (Original) The apparatus of claim 8, further comprising:

means for selecting user interface options to present based on the copy-and-paste operation being between two parts in two different packages.

13. (Currently amended) A storage ~~signal-bearing~~ medium encoded with instructions, wherein the instructions when executed comprise:

receiving a copy-and-paste operation, a selection of a block of code, and a selection of a paste location;

determining that the~~whether a~~ block of code ~~associated with a copy-and-paste operation~~ has a size greater than a threshold;

ROC920030312US1 5
10/728,017

      creating a method that comprises the block of code ~~when the size is greater than the threshold~~;

      replacing the block of code with an invocation of the method; and

      adding the invocation of the method at <u>the paste</u>~~a paste~~ location.

14. (Currently amended) The <u>storage</u>~~signal-bearing~~ medium of claim 13, further comprising:

      selecting user interface options to present based on whether the copy-and-paste operation is within a single part and class.

15. (Currently amended) The <u>storage</u>~~signal-bearing~~ medium of claim 13, further comprising:

      selecting user interface options to present based on whether the copy-and-paste operation is between two parts in a single package.

16. (Currently amended) The <u>storage</u>~~signal-bearing~~ medium of claim 13, further comprising:

      selecting user interface options to present based on the copy-and-paste operation being between two parts in two different packages.

17. (Currently amended) An electronic device comprising:

      a processor; and

      a storage device encoded with instructions, wherein the instructions when executed on the processor comprise:

      <u>receiving a copy-and-paste operation, a selection of a block of code at a copy location, and a selection of a paste location</u>;

      determining <u>that the</u>~~whether a~~ block of code ~~associated with a copy-and-paste operation~~ has a size greater than a ~~threshold,~~<u>threshold</u>;

      creating a method that comprises the block of <u>code;</u>~~code when the size is greater than the threshold,~~

ROC920030312US1   6
10/728,017

      replacing the block of code at the copya copy location with an invocation
of the method,method;

      adding the invocation of the method at the paste location;a paste location,
and

      determining thatwhen the block of code is to return a plurality of
values,values; and

      creating a helper class for the method, wherein the helper class returns the
plurality of valuesor values.

18. (Original) The electronic device of claim 17, wherein the instructions further
comprise:

      selecting a user interface default option to present based on whether the copy-and-
paste operation is between two parts in a single package.

19. (Currently amended) The electronic device of claim 17, wherein the instructions
further comprise:

      designating a create private method option as a user interface default option if the
copy-and-paste operation requested that the block of code be copied within a single part.

      selecting a user interface default option to present based on whether the copy-and-
paste operation is between two parts in a single package.

20. (Original) The electronic device of claim 17, wherein the instructions further
comprise:

      selecting a user interface default option to present based on the copy-and-paste
operation being between two parts in two different packages.